



## LEGEND

1. **PERM-A-BARRIER® VPL 50RS UV STABLE MEMBRANE**
2. ROOF MEMBRANE AND ROOF DETAILS
3. **PERM-A-BARRIER® GRACE ULTRA - PRIME SUBSTRATE WHERE REQUIRED**
4. MASONRY ANCHOR DETAILING (SEE DRAWING VPL50RS-006)
5. MASONRY WEEP/VENT

## NOTE

- CONSULT GCP & ROOFING MANUFACTURER FOR COMPATIBILITY AND CONNECTION AT ROOF INTERFACE

## GENERAL NOTES

1. Detail not suitable for all climates. Avoiding excessive moisture accumulation in exterior walls is dependent on many factors including proper placement of insulation and water, air, and vapor control layers in the wall. Confirm membranes are suitable for project specific service temperatures. For assistance with exterior wall design, consult with a building science professional.
2. Install all GCP products in accordance with GCP Product Data Sheets and GCP recommendations.
3. GCP products are indicated in the detail legend in **BOLDFACE** font. Detail components by others are indicated in GRAY FONT. Install components per manufacturer and project specific requirements.

\*Refer to air barrier system product data sheet for acceptable self-adhered flashing products.

### PARAPET DETAIL - MASONRY CLADDING (ALTERNATE)

PERM-A-BARRIER® VPL 50RS UV STABLE

DRAWING: VPL50RS-007 (ALT)

SCALE: 3" = 1'

EFFECTIVE DATE: 2023.04.10

SUPERCEDES: NEW

