



LEGEND

1. **PERM-A-BARRIER® (RAW EDGE TERMINATED WITH UNIVERSAL FLASHING & SEALANT)**
2. **PERM-A-BARRIER® VPL 50RS UV STABLE MEMBRANE**
3. CLADDING ATTACHMENT, DETAIL PER GCPAT REQUIREMENTS
4. **JOINT TREATMENT PER DRAWING VPL50RS-009B**

NOTE

- AT CMU OR CAST-IN-PLACE CONCRETE CONSTRUCTION, PERM-A-BARRIER ULTRA AT OUTSIDE CORNERS IS OPTIONAL PROVIDED SUBSTRATE ALLOWS FOR CONTINUOUS AND REQUIRED SYSTEM THICKNESS

GENERAL NOTES

1. Detail not suitable for all climates. Avoiding excessive moisture accumulation in exterior walls is dependent on many factors including proper placement of insulation and water, air, and vapor control layers in the wall. Confirm membranes are suitable for project specific service temperatures. For assistance with exterior wall design, consult with a building science professional.
2. Install all GCP products in accordance with GCP Product Data Sheets and GCP recommendations.
3. GCP products are indicated in the detail legend in **BOLDFACE** font. Detail components by others are indicated in GRAY FONT. Install components per manufacturer and project specific requirements.

*Refer to air barrier system product data sheet for acceptable self-adhered flashing products.



OUTSIDE CORNER - NON-MASONRY CLADDING

PERM-A-BARRIER® VPL 50RS UV STABLE

DRAWING: VPL 50RS UV-017

SCALE: 3" = 1'

EFFECTIVE DATE: 2023.09.12

SUPERCEDES: VPL50-017