

Safety Data Sheet

Printing date 02/24/2022

Version Number 1.0

Reviewed on 02/24/2022

Page 1/7

1 Identification

Product identifier

Trade name: PERM-A-BARRIER® Universal Flashing and Sealant

SDS ID Number: 747

Relevant identified uses of the substance or mixture, and uses advised against: Specialty construction product. Not intended for other uses.

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

GCP Applied Technologies 2325 Lakeview Pkwy Alpharetta GA 30009 USA

GCP Canada, Inc. 294 Clements Road W. Ajax, Ontario L1S 3C6 Canada

Information department:

Environmental Health & Safety USA: +1-617-876-1400 (24 hours) +1-800-354-5414 (8AM - 5PM) Not functional within Massachusetts CAN: 1-905-683-8561 (24 hours) Email address: msds.gcp@gcpat.com

Transport Emergency: Chemtrec +1-800-424-9300 (24 hours)

2 Hazard(s) identification

Classification of the substance or mixture

May cause an allergic skin reaction. May damage fertility or the unborn child. Additional information: SDS's are not required for finished articles. Nevertheless, the following information is provided to assist with safe use.

Label elements: The product is classified and labeled according to the Globally Harmonized System (GHS)

Hazard pictograms



Danger

Hazard statements May cause an allergic skin reaction. May damage fertility or the unborn child. Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water. IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information: Avoid breathing dust.

(Cont. on page 2) USGHS

Trade name: PERM-A-BARRIER® Universal Flashing and Sealant

Reviewed on 02/24/2022

(Cont. from page 1)

Hazard description: NFPA ratings (scale 0 - 4)

 $\frac{1}{2} \frac{1}{0}$ Health = 2 Fire = 1 Reactivity = 0

HMIS-ratings (scale 0 - 4)

HEALTH*2FIRE1REACTIVITY1

Health = *2 Flammability = 1 Reactivity = 0

Other hazards Contact with residue from adhesive may cause eye and skin irritation.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3 Composition/information on ingredients

Chemical characterization: Mixture

Description: Mixture of the hazardous substance(s) listed below with additional nonhazardous ingredients.

Hazardous components:		
1317-65-3	Limestone	50-<60%
471-34-1	Calcium carbonate	3-<5%
2768-02-7	Trimethoxyvinylsilane	3-<5%
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	0.1-<1%
22673-19-4	Dibutyltin bis(acetylacetonate)	0.1-<1%
		I

Additional information: Non-hazardous ingredients may be listed in Section 15; Right-To-Know disclosure.

4 First-aid measures

Description of first aid measures

General information: Get medical advice/attention if you feel unwell.

After inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

After skin contact: If skin irritation occurs, consult a doctor.

After eye contact:

Rinse cautiously with water for several minutes. If symptoms persist, consult a physician.

After swallowing:

Rinse mouth.

Do NOT induce vomiting.

Information for doctor:

Most important symptoms and effects, both acute and delayed Allergic reactions

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Cont. on page 3) USGHS

Trade name: PERM-A-BARRIER® Universal Flashing and Sealant

(Cont. from page 2)

Page 3/7

Advice for firefighters

Protective equipment: Wear personal protective equipment.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Methods and material for containment and cleaning up: Pick up mechanically.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling Wash thoroughly after handling.

Avoid eye and skin contact with residue from adhesive.

Release liners are slippery. Remove from work area immediately after membrane application.

Membrane is slippery when wet or covered with frost.

Release liners may cause slip and trip hazards.

Do not eat, drink or smoke when using this product. Wash skin after handling.

For professional use only. Keep out of children's reach.

Information about protection against explosions and fires:

Removal of release liner may generate a static electrical discharge (spark).

Conditions for safe storage, including any incompatibilities

Storage:

Information about storage in one common storage facility: Keep respirator available.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components	Components with limit values that require monitoring at the workplace:		
	1317-65-3 Limestone		
TWA (USA)	Short-term value: 10 mg/m ³ , mg/m ³ ppm Long-term value: 10 mg/m ³ , mg/m ³ ppm (Particulate matter no asbestos)		
471-34-1 Ca	471-34-1 Calcium carbonate		
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction		
	(Cont. on page 4)		

USGHS

Reviewed on 02/24/2022

(Cont. from page 3)

Trade name: PERM-A-BARRIER® Universal Flashing and Sealant

TLV (USA) TLV withdrawn

2768-02-7 Trimethoxyvinylsilane

EV (Canada) Short-term value: 60 mg/m³, 10 ppm

Additional information:

The lists that were valid during the creation were used as basis. Canadian employers must consult the exposure limits in their province.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Avoid contact with the eyes and skin.

The usual precautionary measures for handling chemicals should be followed.

Breathing equipment:

Control exposure to ingredients with workplace control parameters if mentioned above. If no ingredients are listed, respiratory protection is generally not required.

If exposure limits are listed and may be exceeded, use approved respiratory protective equipment and filter type appropriate for the listed ingredients. (NIOSH, CEN, etc.).

Protection of hands: Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Material of gloves

Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product. Rubber or other impervious gloves should be worn to prevent skin contact.

Eye protection:



Safety glasses with side shield protection.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing.

9 Physical and chemical properties

Information on basic physical and chemical properties		
General Information Appearance:		
Form:	Paste	
Color:	Black	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value (~):	Not applicable.	
Change in condition Melting point/Melting range: Boiling point/Boiling range: Flash point:	Undetermined. Undetermined. >140 °C (>284 °F)	
Flammability (solid, gaseous):	Not determined.	
Ignition temperature:	Undetermined.	
Decomposition temperature: Auto igniting: Danger of explosion:	Not determined. Not determined. Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
		(Cont. on page 5)

USGHS

Page 5/7

Trade name: PERM-A-BARRIER® Universal Flashing and Sealant

		(Cont. from page 4)
Vapor pressure:	Not applicable.	
Density: (~)	Not determined.	
Vapor density	Not determined.	
Solubility in / Miscibility with		
Water:	Insoluble.	
Partition coefficient (n-octanol/wat	er): Not determined.	
Viscosity:		
Dynamic:	Not applicable.	
Kinematic:	Not applicable.	
Molecular weight	Not determined.	
Other information	No further relevant information available.	

10 Stability and reactivity

Reactivity

Stable under normal conditions. No further relevant information available.

Chemical stability

Thermal decomposition: No decomposition if used according to specifications.

Possibility of hazardous reactions

No dangerous reactions known. No further relevant information available.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide and carbon dioxide

11 Toxicological information

Information on toxicological effects

Acute toxicity:

Primary irritant effect:

on the skin: No irritating effect expected

on the eye: No irritating effect expected

inhalation: No irritating effect expected

Sensitization: May cause an allergic skin reaction.

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer) Human Carcinogenicity:

Group 1- Positive, Group 2A- Probable, Group 2B- Possible, Group 3- Not Classifiable

1333-86-4 Carbon black 14808-60-7 Quartz (SiO2)

NTP (National Toxicology Program)

K-Known to be carcinogenic, R-May reasonably be anticipated to be carcinogenic

14808-60-7 Quartz (SiO2)

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients are listed.

(Cont. on page 6)

2B

Κ

USGHS

1

Trade name: PERM-A-BARRIER® Universal Flashing and Sealant

Reviewed on 02/24/2022

(Cont. from page 5)

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Not known to be hazardous to water.

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Disposal methods:

Consult all regulations (federal, state, provincial, local) or a qualified waste disposal firm when characterizing product for disposal. Dispose of waste in accordance with all applicable regulations.

Recommendation:



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Dispose of contents/container in accordance with local/regional/national/international regulations.

14 Transport information			
UN-Number DOT, IMDG, IATA	Not applicable.		
UN proper shipping name DOT, IMDG, IATA	Not applicable.		
Transport hazard class(es)			
DOT, IMDG, IATA Class	Not applicable.		
Packing group DOT, IMDG, IATA	Not applicable.		
Environmental hazards:	Not applicable.		
Special precautions for user Not applicable.			
Transport/Additional information:			
DOT Remarks:	Not Regulated.		
UN "Model Regulation":	Not applicable.		
	USGH		

(Cont. on page 7)

(Cont. from page 6)

Page 7/7

Trade name: PERM-A-BARRIER® Universal Flashing and Sealant

15 Regulatory information
Other regulations in domestic and foreign countries SARA (Superfund Amendments and Reauthorization Act)
Section 302/304 (extremely hazardous substances): None of the ingredients is listed.
Section 313 Reportable Ingredients (Chemicals present below reporting threshold are exempt):
None of the ingredients is listed.
SARA Section 312/Tier I & II Hazard Categories: Health Hazard - Reproductive toxicity Health Hazard - Respiratory or Skin Sensitization
North America Chemical Inventory Status
TSCA (Toxic Substances Control Act - United States):
All ingredients are listed or exempt from listing unless otherwise noted below.
CEPA (Canadian DSL):
All ingredients are listed or exempt from listing unless otherwise noted below.
Right to Know Ingredient Disclosure: 1317-65-3 Limestone
1333-86-4 Carbon black
14808-60-7 Quartz (SiO2)
California Proposition 65: (Substances <0.1% unless noted in Section 3)
Chemicals known to cause cancer:
Carbon black
Quartz (SiO2)
Chemicals known to cause reproductive toxicity for females:
None of the ingredients are listed.
Chemicals known to cause reproductive toxicity for males:
None of the ingredients are listed.
Chemicals known to cause developmental toxicity:
None of the ingredients are listed.
Carcinogenicity Categories
TLV-ACGIH (THE American Conference of Governmental Industrial Hygienists) Human Carcinogen - A1 Confirmed, A2 Suspected, A3 Unknown Relevance, A4 Not Classifiable
None of the ingredients are listed.
NIOSH-Cancer (National Institute for Occupational Safety and Health)
1333-86-4 Carbon black
14808-60-7 Quartz (SiO2)
Volatile Organic Compounds (VOC) reported per the Emission Standards. 20 g/L

16 Other information

The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection.

Department issuing SDS:

GCP Applied Technologies 2325 Lakeview Pkwy Alpharetta GA, 30009 USA USA: +1-617-876-1400 (24 hours) +1-800-354-5414

Contact:

The first date of preparation 02/24/2022

Number of revision times and the latest revision date 1.0 / 02/24/2022

USGHS -