

DARAPEL[®] Data Sheet

Integral water repellent admixture

Product Description

DARAPEL[®] admixture is a stable dispersion of stearate and other water repellent compounds that is added into ready mixed concrete during mixing. DARAPEL[®] is a ready-to-use, factory prepared liquid that will simplify handling and eliminate guesswork.

Uses

Architects, engineers, contractors and other authorities agree that even good quality concretes, mortars, etc. that are properly placed, set or applied then cured, are inherently porous or permeable to water. The free passage of moisture occurs in pores formed during and after placing. DARAPEL[®] forms an internal barrier against water transmission in mixes used for ready mixed or precast concrete.

Performance

The addition of DARAPEL[®] to the mix will provide hydrophobic (water-repelling) properties. The water insoluble stearate acts as a non-wettable lining on the walls of all pores and voids in the mix, making them water repellent. The DARAPEL[®] “built-in” water barriers guard against damage caused by water infiltration.

Improved Product Quality

Higher quality concrete will result from the use of DARAPEL[®]. The workability of mixes will be improved especially in low cement content concrete mixes. The protection of embedded steel and resistance to bacteria or fungus growth may also be increased by keeping the concrete drier.

Product Advantages

The addition of DARAPEL[®] will reduce the amount of water that permeates through the concrete. Reducing the passage of water will provide beneficial advantages by:

- Increasing resistance to weathering
 - wetting and drying
 - freezing and thawing
- Increase resistance to chemical attack
- Reduce the potential for efflorescence
- Reduce the probability of corrosion of embedded meta

Air Content

Added by itself, DARAPEL[®] may have a slight effect on the entrained air volume. Trial mixes or field tests are recommended to evaluate its effect with your material at your plant. Over-dosing can cause variations in air content.

Curing

Proper curing of the in-place mix is vital. Allowing the mix to prematurely dry out should be prevented because re-wetting (and continued hydration) may not be effective.

Dispensing Equipment

It is recommended that DARAPEL[®] be dispensed into the concrete and thoroughly mixed to provide complete dispersion. DARAPEL[®] can be added at any point during the charging of the mixer.

A complete line of automated, high precision dispensing equipment is available for plant installation through your GCP admixtures representative.

Packaging and Handling

DARAPEL[®] is available in totes, drums and pails.

DARAPEL[®] will freeze at approximately 32°F (0°C) and cannot be remixed after freezing.

Flammability

None.

Addition Rates

The amount of DARAPEL[®] necessary for a specific mix depends upon the degree of water repellency desired. Suggested addition rates for DARAPEL[®] in ready mixed or precast concrete are 3.0 to 6.0 fl oz/100 lb (190 to 390 mL/100 kg) of cement.

Compatibility with Other Admixtures and Batch Sequencing

DARAPEL[®] can be added to mixes containing other admixtures. Testing with actual materials should be done to determine performance. Each admixture must be added separately to the mix. Do not allow any of the admixtures to contact each other before they enter the mix.

The GCP Advantage in Admixtures

DARAPEL[®] was developed by GCP Applied Technologies - recognized world-wide as a leader in concrete admixture technology. Pioneers in this specialized field for over 50 years, we operate one of the largest privately owned cement and concrete research laboratories.

Our admixtures are manufactured in modern U.S. and Canadian plants, under strict quality controls which assure their quality, uniformity and performance. Highly trained GCP admixture specialists are ready to assist you in their use.

Today, when so much depends on every element of a construction project, you can rely on the special combination of experience, product quality and technical support which are the "GCP Advantage" in admixtures.

gcpat.com | North America Customer Service: 1 877-4AD-MIX1 (1 877-423-6491)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

DARAPEL is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Suite 450, Alpharetta, GA 30009, USA

GCP Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6

This document is only current as of the last updated date stated below and is valid only for use in the United States. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2022-08-17

gcpat.com/solutions/products/darapel-data-sheet