

PIERI[®] EURO-WAX Data Sheet

Form Release Agent

Product Description

PIERI[®] EURO-WAX is a semi-liquid, high performance visco-elastic form release agent that ensures high quality architectural surfaces. PIERI[®] EURO-WAX will not stain concrete or affect adhesion of waterproofing or other coatings. Coverage: 5,000-10,000 ft²/gal (123-245 m²/L).

Uses

PIERI[®] EURO-WAX is formulated for use with the most intricate molds and forms; especially with no or low draft for release. PIERI[®] EURO-WAX may be used with all types of forms, including plastic, rubber, latex as well as Styrofoam and is particularly useful in all self-consolidating concrete (SCC) concrete applications.

PIERI[®] EURO-WAX is a low odor, viscous liquid that may be used at low and high temperatures.

It is a non-staining, rain resistant and provides corrosion inhibiting cabability, without creating powdery residue.

Directions for Use

Apply a extremely thin coat with rag, sponge or mop. Can only be spray applied with airless equipment.

The usage of PIERI[®] EURO-WAX results in clean, uniform surfaces with little or no cleanup required.

Packaging & Handling

PIERI[®] EURO-WAX is available in 55 gallon (208 L) drums and 5 gallon (19 L) pails. PIERI[®] EURO-WAX has a shelf life of one year from date of manufacture if stored in in a cool dry place in its closed original container. Keep away from all sources of heat, sparks or flame.

Physical Specifications

Flash Point: 115°F (46°C)

Specific Gravity: 0.80

Safety

Read SDS before use.



North America customer service: 1-877-4AD-MIX (1-877-423-6491)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

PIERI is a registered trademark, which may be registered in the United States and/orother countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Suite 475, Alpharetta, GA 30009, USA

GCP Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6

This document is only current as of the last updated date stated below and is valid only for use in the United States. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.