

SA1030 Bond Coat Data Sheet

POLYMER-MODIFIED BOND COAT

Product Description

SA1030 Bond Coat is a polymer-modified bond coat, applied over the ELIMINATOR® waterproofing membrane to provide a very strong bond between the membrane and hot bituminous road surfacing.

Uses

SA1030 Bond Coat is applied to the ELIMINATOR® waterproofing membrane to provide a bond between the membrane and the bituminous wearing course. It is recommended where the bitumen content in the surfacing specification is low and/or where the surfacing layer is thin.

Features

- Provides an excellent bond between the ELIMINATOR® waterproofing membrane and the surfacing
- Solidifies ELIMINATOR® rapidly after application

Technical Data

Property	Value
Material application temperature	350 °F to 375 °F
Minimum activation temperature	200 °F
Minimum overcoating time for application of surfacing	30 minutes

Surface Preparation

SA1030 Bond Coat is applied direct to the cured ELIMINATOR® membrane, which must be clean and free from loose debris, moisture and contaminants.

Application

1. The applied SA1030 Bond Coat must be allowed to cool fully to the ambient temperature for a minimum of 30 minutes after application before surfacing can commence.
2. The rolling temperature of the surfacing must not fall below the minimum SA1030 Bond Coat reactivation temperature of 200°F.
3. SA1030 Bond Coat must be clean and free from all contaminants and standing water during surfacing.
4. The mechanical action of the asphalt-paving machine on the SA1030 Bond Coat must be kept to a minimum. Wherever possible, a paving machine with pneumatic or balloon tires should be used. Extra care must be taken if using a tracked paving vehicle, as this form of traction increases the possibility of pickup of the tack coat.
5. The wheels or tracks of the paving machine must be kept clean and sprayed regularly with a detergent/water solution at a ratio of 1:100, to minimize the risk of their sticking to the tack coat.
6. The wheels of all asphalt delivery vehicles must also be inspected, cleaned and sprayed with the detergent/water solution at ratio of 1:100, before being allowed to drive on the tack coat.
7. Vehicles remaining stationary on the SA1030 Bond Coat should be avoided, particularly pavers with heat and vehicles that have traversed freshly-applied hot asphalt. If operations are stopped or delayed, all vehicles should be removed from the tack coat or their wheels isolated from the tack coat with protection boards.

Coverage

- SA1030 Bond Coat is applied at a rate of 140 ft² /50lb box, equal to 25-35 ft² /gal.

Packaging & Storing

SA1030 Bond Coat is supplied in cardboard tubes and should be stored in cool, dry, protected conditions, out of direct sunlight and in accordance with the relevant site health and safety regulations. Storage temperature should not exceed 77°F. Storage at elevated temperatures may cause deformation of the cardboard packaging. Although this is best avoided, it will have no detrimental effect on the performance of the material.

Do not store near open flames or foodstuffs.

Stored in unopened containers, under these conditions, the components have a shelf life of twelve months.

Health & Safety

Read and understand the product label and safety data sheet (SDS) for each system component. All users should acquaint themselves with this information prior to working with the products and follow the precautionary statements. SDSs can be obtained by contacting your local GCP representative or office, by calling GCP toll free at 1-866-333-3SBM (3726) and in some cases from our web site at gcpat.com.

Important Information for General Contractors and Paving Contractors

General contractors and surfacing contractors applying hot rolled asphalt over Stirling Lloyd's SA1030 Bond Coat and ELIMINATOR® bridge deck waterproofing system must follow the information given below. It is important that this guidance is followed to reduce or minimize any risk of tack coat pick up on the wheels of vehicles involved in the paving, since the adhesive properties of SA1030 Bond Coat are formed by heat.

General Information

SA1030 Bond Coat is part of a wide range of specialist waterproofing, surfacing and repair materials manufactured and supplied by GCP. If you require any further information on this or any other of our products, please contact Technical Services or visit www.gcpat.com

gcpat.com | North America customer service: 1-866-333-3726

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation or suggestion is intended for any use that would infringe any patent, copyright or other third-party right.

ELIMINATOR® is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2019 GCP Applied Technologies, Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Suite 400, Alpharetta, GA 30009, USA

GCP Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6

This document is only current as of the last updated date stated below and is valid only for use in the United States. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.com. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-10-09

gcpat.com/solutions/products/eliminator-bridge-deck-waterproofing-membrane/sa1030-bond-coat-data-sheet