

Pallet Lub 205

Chemicals for Concrete Production Equipment

Pallet Lube 205 Description

Pallet Lub 205 is a blend of tall oil resins and wetting agents specifically formulated to create a smooth, slippery barrier between the metal surface of the pallet and the concrete. On a pallet turning machine, the action of the turner tends to increase the effectiveness of this barrier.

Pallet Lub 205 is an extremely effective release agent for the top ring, spindle, and pallet of a pipe machine. Pallet Lub 205 is a non-flammable water-based material that eliminates the precautions required by hazardous, quick drying pallet compounds.

Directions for Use

Clean pallet well, making sure previous build-up and oils are completely removed. Apply a light coating of Pallet Lub 205 with the use of a rag or brush. Before the next application, a light pass with steel wool is helpful. Pallet Lub 205 may be diluted 1:1 with water for certain applications.

Health and Safety

All precautions defined on the SDS (Safety Data Sheet) for Pallet Lub 205 must be followed.

Packaging and Handling

55 U.S. gal (208 L) drums weighing 510 lbs (231 kg)

gcpat.com | Customer Service: 1-877-4ADMIX1 (1-877-423-6491)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

© Copyright 2016 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA.