



BXUV.X854

Design/System/Construction/Assembly Usage Disclaimer

- Authorities Having Jurisdiction should be consulted in all cases as to the particular requirements covering the installation and use of UL Certified products, equipment, system, devices, and materials.
- Authorities Having Jurisdiction should be consulted before construction.
- Fire resistance assemblies and products are developed by the design submitter and have been investigated by UL for compliance with applicable requirements. The published information cannot always address every construction nuance encountered in the field.
- When field issues arise, it is recommended the first contact for assistance be the technical service staff provided by the product manufacturer noted for the design. Users of fire resistance assemblies are advised to consult the general Guide Information for each product category and each group of assemblies. The Guide Information includes specifics concerning alternate materials and alternate methods of construction.
- Only products which bear UL's Mark are considered Certified.

BXUV - Fire Resistance Ratings - ANSI/UL 263 Certified for United States

BXUV7 - Fire Resistance Ratings - CAN/ULC-S101 Certified for Canada

See General Information for Fire-resistance Ratings - ANSI/UL 263 Certified for United States
Design Criteria and Allowable Variances


See General Information for Fire Resistance Ratings - CAN/ULC-S101 Certified for Canada
Design Criteria and Allowable Variances

Design No. X854

July 12, 2019

Ratings — 1, 1-1/2, 2, 3 and 4 h.

*** Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (such as Canada), respectively.**



1. Spray-Applied Fire Resistive Materials* — Applied by mixing with water and spraying in more than one coat to the thicknesses shown below, to steel surfaces which are clean and free of dirt, loose scale, and oil. Min avg and min ind density of 15/14 pcf respectively. Min avg and min ind density of 22/19 pcf respectively for Types Z-106, Z-106/G, Z-106/HY. Min avg and min ind density of 40/36 pcf respectively for Types Z-146, Z-146PC and Z-146T cementitious mixture. Min avg and min ind density of 50/45 pcf respectively for Types Z-156, Z-156T and Z-156PC. For method of density determination, see Design Information Section, Sprayed Material.

The thickness of Spray-Applied Fire Resistive Materials to be applied to all surfaces of the column (Item 1) required for rating periods of 1 h, 1-1/2 h, 2 h, 3 h, 4 h may be determined by the equation:

$$h = \frac{R}{1.05 (W/D) + 0.61}$$

Where:

h = Spray-Applied Fire Resistive Materials thickness in the range 0.25-3.875 in.

R = Fire resistance rating in hours (1 - 4 h)

D = Heated perimeter of steel column in inches

W = Weight of steel column in lbs per foot

W/D = 0.338 to 6.76

As an alternate to the equation, the minimum thickness of Spray-Applied Fire Resistive Materials required for various fire resistance ratings of contour sprayed or boxed columns may be determined from the table below:

TABLE 1

Col Size	W/D	Min Thk (In.)				
		1 Hr	1-1/2 Hr	2 Hr	3 Hr	4 Hr
W4x13	0.556	11/16	1-3/16	1-5/8	2-1/2	3-3/8
W5x16	0.55	11/16	1-3/16	1-5/8	2-1/2	3-3/8
W5x19	0.644	5/8	1-1/8	1-7/16	2-5/16	3-1/8
W6x9	0.338	15/16	1-1/2	2	2-1/2	3-13/16
W6x12	0.448	13/16	1-3/8	1-13/16	2-1/2	3-3/4
W6x15	0.431	13/16	1-3/8	1-13/16	2-1/2	3-13/16

W6x16	0.584	11/16	1-3/16	1-9/16	2-7/16	3-5/16
W6x20	0.563	11/16	1-3/16	1-9/16	2-1/2	3-3/8
W6x25	0.696	5/8	1-1/16	1-3/8	2	2-11/16
W8x13	0.421	13/16	1-3/8	1-7/8	2-1/2	3-13/16
W8x15	0.481	3/4	1-5/16	1-3/4	2-1/2	3-5/8
W8x18	0.499	3/4	1-1/4	1-11/16	2-1/2	3-1/2
W8x21	0.577	11/16	1-3/16	1-9/16	2-1/2	3-5/16
W8x24	0.591	11/16	1-1/8	1-9/16	2-7/16	3-5/16
W8x28	0.688	5/8	1-1/16	1-3/8	2	2-11/16
W8x31	0.665	5/8	1-1/16	1-7/16	2-5/16	3-1/16
W8x35	0.749	9/16	1	1-5/16	2	2-11/16
W8x40	0.849	9/16	3/4	1-1/8	1-11/16	2-1/2
W8x48	1	1/2	3/4	1	1-11/16	2-5/16
W8x58	1.2	7/16	3/4	13/16	1-3/8	1-15/16
W8x67	1.37	3/8	5/8	3/4	1-1/4	1-11/16
W10x12	0.347	7/8	1-1/2	2	2-1/2	3-13/16
W10x15	0.429	13/16	1-3/8	1-7/8	2-1/2	3-13/16
W10x17	0.482	3/4	1-5/16	1-3/4	2-1/2	3-5/8
W10x19	0.538	3/4	1-1/4	1-5/8	2-1/2	3 7/16
W10x22	0.523	3/4	1-1/4	1-11/16	2-1/2	3-1/2
W10x26	0.612	11/16	1-1/8	1-1/2	2-3/8	3-1/4
W10x30	0.699	5/8	1-1/16	1-3/8	2	2-11/16
W10x33	0.661	5/8	1-1/16	1-7/16	2-5/16	3-1/8
W10x39	0.78	9/16	1	1-1/4	2	2-11/16
W10x45	0.888	1/2	3/4	1-1/8	1-11/16	2-1/2
W10x49	0.84	9/16	3/4	1-1/8	1-11/16	2-1/2
W10x54	0.922	1/2	3/4	1-1/16	1-11/16	2-1/2
W10x60	1.01	1/2	3/4	1	1-5/8	2-5/16
W10x68	1.15	7/16	3/4	7/8	1-7/16	2
W10x77	1.28	7/16	11/16	3/4	1-5/16	1-13/16
W10x88	1.45	3/8	5/8	11/16	1-3/16	1-5/8

W10x100	1.64	3/8	9/16	11/16	1-1/8	1-1/2
W10x112	1.81	5/16	1/2	11/16	1-1/8	1-1/2
W12x14	0.363	7/8	1-1/2	2	2-1/2	3-13/16
W12x16	0.41	13/16	1-7/16	1-7/8	2-1/2	3-13/16
W12x19	0.485	3/4	1-5/16	1-3/4	2-1/2	3-5/8
W12x22	0.56	11/16	1-3/16	1-5/8	2-1/2	3-3/8
W12x26	0.531	3/4	1-1/4	1-5/8	2-1/2	3 7/16
W12x30	0.607	11/16	1-1/8	1-1/2	2-7/16	3-1/4
W12x35	0.703	5/8	1-1/16	1-3/8	2	2-11/16
W12x40	0.734	5/8	1	1-5/16	2	2-11/16
W12x45	0.829	9/16	15/16	1-3/16	1-15/16	2-11/16
W12x50	0.909	1/2	3/4	1-1/16	1-11/16	2-1/2
W12x53	0.855	9/16	3/4	1-1/8	1-11/16	2-1/2
W12x58	0.925	1/2	3/4	1-1/16	1-11/16	2-7/16
W12x65	0.925	1/2	3/4	1-1/16	1-11/16	2-7/16
W12x72	1.02	1/2	3/4	15/16	1-5/8	2-1/4
W12x79	1.11	7/16	3/4	7/8	1-1/2	2-1/8
W12x87	1.22	7/16	11/16	13/16	1-3/8	1-15/16
W12x96	1.34	3/8	11/16	3/4	1-1/4	1-3/4
W12x106	1.47	3/8	5/8	11/16	1-3/16	1-5/8
W12x120	1.65	5/16	9/16	11/16	1-1/8	1-1/2
W12x136	1.86	5/16	1/2	11/16	1-1/8	1-1/2
W12x152	2.04	5/16	1/2	11/16	1-1/16	1-7/16
W12x170	2.26	1/4	7/16	5/8	15/16	1-5/16
W12x190	2.5	1/4	5/16	9/16	7/8	1-3/16
W12x210	2.73	1/4	5/16	1/2	13/16	1-1/8
W12x230	2.96	1/4	5/16	1/2	3/4	1-1/16
W12x252	3.2	1/4	5/16	7/16	3/4	1
W12x279	3.5	1/4	5/16	7/16	11/16	7/8
W12x305	3.76	1/4	5/16	3/8	5/8	7/8
W12x336	4.06	1/4	1/4	3/8	9/16	13/16

W14x22	0.476	3/4	1-5/16	1-3/4	2-1/2	3-5/8
W14x26	0.559	11/16	1-3/16	1-5/8	2-1/2	3-3/8
W14x30	0.562	11/16	1-3/16	1-9/16	2-1/2	3-3/8
W14x34	0.633	5/8	1-1/8	1-7/16	2-3/8	3 3/16
W14x38	0.706	5/8	1-1/16	1-3/8	2	2-11/16
W14x43	0.752	9/16	1	1-5/16	2	2-11/16
W14x48	0.835	9/16	15/16	1-3/16	1-15/16	2-11/16
W14x53	0.915	1/2	3/4	1-1/16	1-11/16	2-1/2
W14x61	0.928	1/2	3/4	1-1/16	1-11/16	2-7/16
W14x68	1.04	1/2	3/4	15/16	1-5/8	2-1/4
W14x74	1.12	7/16	3/4	7/8	1-1/2	2-1/16
W14x82	1.23	7/16	11/16	13/16	1-3/8	1-7/8
W14x90	1.08	7/16	3/4	7/8	1-9/16	2-1/8
W14x99	1.18	7/16	3/4	13/16	1-7/16	2
W14x109	1.29	7/16	11/16	3/4	1-5/16	1-13/16
W14x120	1.42	3/8	5/8	3/4	1-3/16	1-11/16
W14x132	1.56	3/8	9/16	11/16	1-1/8	1-9/16
W14x145	1.64	3/8	9/16	11/16	1-1/8	1-1/2
W14x159	1.78	5/16	9/16	11/16	1-1/8	1-1/2
W14x176	1.96	5/16	1/2	11/16	1-1/16	1-1/2
W14x193	2.14	5/16	7/16	5/8	1	1-3/8
W14x211	2.32	1/4	7/16	5/8	15/16	1-5/16
W14x233	2.55	1/4	5/16	9/16	7/8	1-3/16
W14x257	2.78	1/4	5/16	1/2	13/16	1-1/8
W14x283	3.03	1/4	5/16	1/2	3/4	1
W14x311	3.3	1/4	5/16	7/16	11/16	15/16
W14x342	3.58	1/4	5/16	7/16	5/8	7/8
W14x370	3.84	1/4	5/16	3/8	5/8	13/16
W14x398	4.09	1/4	1/4	3/8	9/16	13/16
W14x426	4.32	1/4	1/4	3/8	9/16	3/4
W14x455	4.59	1/4	1/4	5/16	1/2	11/16

W14x500	4.95	1/4	1/4	5/16	1/2	11/16
W14x550	5.34	1/4	1/4	5/16	7/16	5/8
W14x605	5.82	1/4	1/4	1/4	7/16	9/16
W14x665	6.21	1/4	1/4	1/4	3/8	9/16
W14x730	6.76	1/4	1/4	1/4	3/8	1/2
W16x26	0.499	3/4	1-1/4	1-11/16	2-1/2	3-1/2
W16x31	0.592	11/16	1-1/8	1-9/16	2-7/16	3-1/4
W16x36	0.617	11/16	1-1/8	1-1/2	2-3/8	3 3/16
W16x40	0.686	5/8	1-1/16	1-3/8	2-1/4	3-1/16
W16x45	0.767	9/16	1	1-1/4	2	2-11/16
W16x50	0.846	9/16	3/4	1-1/8	1-11/16	2-1/2
W16x57	0.963	1/2	3/4	1	1-11/16	2-3/8
W16x67	0.936	1/2	3/4	1-1/16	1-11/16	2-7/16
W16x77	1.07	7/16	3/4	15/16	1-9/16	2-3/16
W16x89	1.22	7/16	11/16	13/16	1-3/8	1-15/16
W16x100	1.37	3/8	5/8	3/4	1-1/4	1-11/16
W18x35	0.602	11/16	1-1/8	1-1/2	2-7/16	3-1/4
W18x40	0.688	5/8	1-1/16	1-3/8	2	2-11/16
W18x46	0.786	9/16	15/16	1-1/4	2	2-11/16
W18x50	0.778	9/16	1	1-1/4	2	2-11/16
W18x55	0.85	9/16	3/4	1-1/8	1-11/16	2-1/2
W18x60	0.923	1/2	3/4	1-1/16	1-11/16	2-7/16
W18x65	0.997	1/2	3/4	1	1-11/16	2-5/16
W18x71	1.08	7/16	3/4	7/8	1-9/16	2-1/8
W18x76	0.971	1/2	3/4	1	1-11/16	2-3/8
W18x86	1.09	7/16	3/4	7/8	1-9/16	2-1/8
W18x97	1.22	7/16	11/16	13/16	1-3/8	1-15/16
W18x106	1.33	3/8	11/16	3/4	1-1/4	1-3/4
W18x119	1.48	3/8	5/8	11/16	1-3/16	1-5/8
W21x44	0.672	5/8	1-1/16	1-3/8	2-1/4	3-1/16
W21x50	0.754	9/16	1	1-1/4	2	2-11/16

W21x57	0.857	9/16	3/4	1-1/8	1-11/16	2-1/2
W21x62	0.846	9/16	3/4	1-1/8	1-11/16	2-1/2
W21x68	0.926	1/2	3/4	1-1/16	1-11/16	2-7/16
W21x73	0.989	1/2	3/4	1	1-11/16	2-5/16
W21x83	1.12	7/16	3/4	7/8	1-1/2	2-1/16
W21x93	1.24	7/16	11/16	13/16	1-3/8	1-7/8
W21x101	1.13	7/16	3/4	7/8	1-1/2	2-1/16
W21x111	1.24	7/16	11/16	13/16	1-3/8	1-7/8
W21x122	1.35	3/8	11/16	3/4	1-1/4	1-3/4
W21x132	1.45	3/8	5/8	11/16	1-3/16	1-5/8
W21x147	1.61	3/8	9/16	11/16	1-1/8	1-1/2
W24x55	0.749	9/16	1	1-5/16	2	2-11/16
W24x62	0.844	9/16	3/4	1-1/8	1-11/16	2-1/2
W24x68	0.837	9/16	15/16	1-3/16	1-15/16	2-11/16
W24x76	0.933	1/2	3/4	1-1/16	1-11/16	2-7/16
W24x84	1.02	1/2	3/4	15/16	1-5/8	2-1/4
W24x94	1.14	7/16	3/4	7/8	1-1/2	2-1/16
W24x104	1.07	7/16	3/4	15/16	1-9/16	2-3/16
W24x117	1.2	7/16	3/4	13/16	1-3/8	1-15/16
W24x131	1.33	3/8	11/16	3/4	1-1/4	1-3/4
W24x146	1.48	3/8	5/8	11/16	1-3/16	1-5/8
W24x162	1.63	3/8	9/16	11/16	1-1/8	1-1/2
W27x84	0.921	1/2	3/4	1-1/16	1-11/16	2-1/2
W27x94	1.03	1/2	3/4	15/16	1-5/8	2-1/4
W27x102	1.11	7/16	3/4	7/8	1-1/2	2-1/8
W27x114	1.23	7/16	11/16	13/16	1-3/8	1-7/8
W27x146	1.35	3/8	11/16	3/4	1-1/4	1-3/4
W27x161	1.48	3/8	5/8	11/16	1-3/16	1-5/8
W27x178	1.63	3/8	9/16	11/16	1-1/8	1-1/2
W30x99	1	1/2	3/4	1	1-11/16	2-5/16
W30x108	1.09	7/16	3/4	7/8	1-9/16	2-1/8

W30x116	1.16	7/16	3/4	13/16	1-7/16	2
W30x124	1.24	7/16	11/16	13/16	1-3/8	1-7/8
W30x132	1.32	3/8	11/16	3/4	1-1/4	1-3/4
W30x173	1.47	3/8	5/8	11/16	1-3/16	1-5/8
W30x191	1.62	3/8	9/16	11/16	1-1/8	1-1/2
W30x211	1.76	5/16	9/16	11/16	1-1/8	1-1/2
W33x118	1.08	7/16	3/4	7/8	1-9/16	2-1/8
W33x130	1.18	7/16	3/4	13/16	1-7/16	2
W33x141	1.28	7/16	11/16	3/4	1-5/16	1-13/16
W33x152	1.37	3/8	5/8	3/4	1-1/4	1-11/16
W33x201	1.58	3/8	9/16	11/16	1-1/8	1-1/2
W33x221	1.73	5/16	9/16	11/16	1-1/8	1-1/2
W33x241	1.87	5/16	1/2	11/16	1-1/8	1-1/2
W36x135	1.15	7/16	3/4	7/8	1-7/16	2
W36x150	1.27	7/16	11/16	3/4	1-5/16	1-7/8
W36x160	1.35	3/8	11/16	3/4	1-1/4	1-3/4
W36x170	1.43	3/8	5/8	3/4	1-3/16	1-5/8
W36x182	1.52	3/8	5/8	11/16	1-1/8	1-9/16
W36x194	1.62	3/8	9/16	11/16	1-1/8	1-1/2
W36x210	1.74	5/16	9/16	11/16	1-1/8	1-1/2
W36x230	1.69	5/16	9/16	11/16	1-1/8	1-1/2
W36x245	1.79	5/16	9/16	11/16	1-1/8	1-1/2
W36x260	1.9	5/16	1/2	11/16	1-1/8	1-1/2
W36x280	2.03	5/16	1/2	11/16	1-1/16	1-7/16
W36x300	2.17	1/4	7/16	5/8	1	1-3/8

The thicknesses contained in the table below are applicable when the Spray-Applied Fire Resistive Materials applied to columns' flange tips are reduced to one-half that shown in the table below:

TABLE 2

Member	Min Col Size	W/D	Half Flange Tip Thickness			
			1 hr	1.5 hr	2 hr	3 hr
W4x13	0.556	7/8	1 5/16	1-11/16	2 9/16	3 3/8
W5x16	0.550	7/8	1 5/16	1-11/16	2 9/16	3 3/8

W5x19	0.644	13/16	1 3/16	1 9/16	2 3/8	3 1/8
W6x9	0.338	1-1/8	1 5/8	2 1/16	3 1/8	4 3/16
W6x12	0.448	15/16	1 7/16	1 7/8	2 13/16	3-13/16
W6x15	0.431	1	1 7/16	1-15/16	2 7/8	3-14/16
W6x16	0.584	7/8	1 1/4	1-11/16	2 1/2	3 5/16
W6x20	0.563	7/8	1 1/4	1-11/16	2 1/2	3 3/8
W6x25	0.696	3/4	1 1/8	1 1/2	2 1/4	2 15/16
W8x13	0.421	1	1 7/16	1-15/16	2 7/8	3-14/16
W8x15	0.481	15/16	1 3/8	1-13/16	2 3/4	3 11/16
W8x18	0.499	15/16	1 3/8	1-13/16	2-11/16	3 9/16
W8x21	0.577	7/8	1 1/4	1-11/16	2 1/2	3 5/16
W8x24	0.591	7/8	1 1/4	1-11/16	2 1/2	3 5/16
W8x28	0.688	13/16	1 3/16	1 1/2	2 1/4	2 15/16
W8x31	0.665	13/16	1 3/16	1 9/16	2 5/16	3 1/16
W8x35	0.749	3/4	1 1/8	1 7/16	2 3/16	2 7/8
W8x40	0.849	11/16	1	1 3/8	2	2-11/16
W8x48	1.000	5/8	15/16	1 1/4	1-13/16	2 7/16
W8x58	1.200	9/16	13/16	1 1/8	1 5/8	2 3/16
W8x67	1.370	1/2	3/4	1	1 1/2	2
W10x12	0.347	1-1/16	1 9/16	2 1/16	3 1/8	4 3/16
W10x15	0.429	1	1 7/16	1-15/16	2 7/8	3-14/16
W10x17	0.482	15/16	1 3/8	1-13/16	2 3/4	3 11/16
W10x19	0.538	7/8	1 5/16	1 3/4	2 9/16	3 7/16
W10x22	0.523	7/8	1 5/16	1 3/4	2 5/8	3 1/2
W10x26	0.612	13/16	1 1/4	1 5/8	2 7/16	3 1/4
W10x30	0.699	3/4	1 1/8	1 1/2	2 1/4	2 15/16
W10x33	0.661	13/16	1 3/16	1 9/16	2 5/16	3 1/8
W10x39	0.780	3/4	1 1/16	1 7/16	2 1/8	2 13/16
W10x45	0.888	11/16	1	1 5/16	2	2 5/8
W10x49	0.840	11/16	1 1/16	1 3/8	2 1/16	2-11/16
W10x54	0.922	11/16	1	1 5/16	1-15/16	2 9/16

W10x60	1.010	5/8	15/16	1 1/4	1-13/16	2 7/16
W10x68	1.150	9/16	7/8	1 1/8	1-11/16	2 1/4
W10x77	1.280	9/16	13/16	1 1/16	1 9/16	2 1/16
W10x88	1.450	1/2	3/4	1	1 7/16	1-15/16
W10x100	1.640	7/16	11/16	7/8	1 5/16	1 3/4
W10x112	1.810	7/16	5/8	13/16	1 1/4	1 5/8
W12x14	0.363	1-1/16	1 9/16	2 1/16	3 1/16	4 1/8
W12x16	0.410	1	1 1/2	1-15/16	2 15/16	3-15/16
W12x19	0.485	15/16	1 3/8	1-13/16	2-11/16	3 5/8
W12x22	0.560	7/8	1 5/16	1-11/16	2 9/16	3 3/8
W12x26	0.531	7/8	1 5/16	1 3/4	2 5/8	3 7/16
W12x30	0.607	13/16	1 1/4	1 5/8	2 7/16	3 1/4
W12x35	0.703	3/4	1 1/8	1 1/2	2 1/4	2 15/16
W12x40	0.734	3/4	1 1/8	1 1/2	2 3/16	2 15/16
W12x45	0.829	11/16	1 1/16	1 3/8	2 1/16	2 3/4
W12x50	0.909	11/16	1	1 5/16	1-15/16	2 9/16
W12x53	0.855	11/16	1	1 3/8	2	2-11/16
W12x58	0.925	11/16	1	1 5/16	1-15/16	2 9/16
W12x65	0.925	11/16	1	1 5/16	1-15/16	2 9/16
W12x72	1.020	5/8	15/16	1 1/4	1-13/16	2 7/16
W12x79	1.110	5/8	7/8	1 3/16	1 3/4	2 5/16
W12x87	1.220	9/16	13/16	1 1/16	1 5/8	2 1/8
W12x96	1.340	1/2	3/4	1	1 1/2	2
W12x106	1.470	1/2	3/4	15/16	1 7/16	1 7/8
W12x120	1.650	7/16	11/16	7/8	1 5/16	1 3/4
W12x136	1.860	7/16	5/8	13/16	1 3/16	1 9/16
W12x152	2.040	3/8	9/16	3/4	1 1/8	1 1/2
W12x170	2.260	3/8	9/16	11/16	1 1/16	1 3/8
W12x190	2.500	5/16	1/2	5/8	15/16	1 1/4
W12x210	2.730	5/16	7/16	5/8	7/8	1 3/16
W12x230	2.960	5/16	7/16	9/16	13/16	1 1/8

W12x252	3.200	5/16	7/16	9/16	13/16	1 1/16
W12x279	3.500	1/4	3/8	1/2	3/4	15/16
W12x305	3.760	1/4	3/8	1/2	11/16	15/16
W12x336	4.060	1/4	5/16	7/16	5/8	7/8
W14x22	0.476	15/16	1 3/8	1-13/16	2 3/4	3 11/16
W14x26	0.559	7/8	1 5/16	1-11/16	2 9/16	3 3/8
W14x30	0.562	7/8	1 1/4	1-11/16	2 1/2	3 3/8
W14x34	0.633	13/16	1 3/16	1 5/8	2 3/8	3 3/16
W14x38	0.706	3/4	1 1/8	1 1/2	2 1/4	2 15/16
W14x43	0.752	3/4	1 1/8	1 7/16	2 3/16	2 7/8
W14x48	0.835	11/16	1 1/16	1 3/8	2 1/16	2 3/4
W14x53	0.915	11/16	1	1 5/16	1-15/16	2 9/16
W14x61	0.928	11/16	1	1 5/16	1-15/16	2 9/16
W14x68	1.040	5/8	15/16	1 3/16	1-13/16	2 3/8
W14x74	1.120	9/16	7/8	1 1/8	1-11/16	2 1/4
W14x82	1.230	9/16	13/16	1 1/16	1 5/8	2 1/8
W14x90	1.080	5/8	7/8	1 3/16	1 3/4	2 5/16
W14x99	1.180	9/16	13/16	1 1/8	1 5/8	2 3/16
W14x109	1.290	9/16	13/16	1 1/16	1 9/16	2 1/16
W14x120	1.420	1/2	3/4	1	1 7/16	1-15/16
W14x132	1.560	1/2	11/16	15/16	1 3/8	1-13/16
W14x145	1.640	7/16	11/16	7/8	1 5/16	1 3/4
W14x159	1.780	7/16	5/8	13/16	1 1/4	1 5/8
W14x176	1.960	3/8	9/16	3/4	1 1/8	1 1/2
W14x193	2.140	3/8	9/16	3/4	1 1/16	1 7/16
W14x211	2.320	3/8	1/2	11/16	1	1 3/8
W14x233	2.550	5/16	1/2	5/8	15/16	1 1/4
W14x257	2.780	5/16	7/16	5/8	7/8	1 3/16
W14x283	3.030	5/16	7/16	9/16	13/16	1 1/16
W14x311	3.300	1/4	3/8	1/2	3/4	1
W14x342	3.580	1/4	3/8	1/2	11/16	15/16

W14x370	3.840	1/4	3/8	7/16	11/16	7/8
W14x398	4.090	1/4	5/16	7/16	5/8	7/8
W14x426	4.320	1/4	5/16	7/16	5/8	13/16
W14x455	4.590	1/4	5/16	3/8	9/16	3/4
W14x500	4.950	1/4	5/16	3/8	9/16	3/4
W14x550	5.340	1/4	1/4	3/8	1/2	11/16
W14x605	5.820	1/4	1/4	5/16	1/2	5/8
W14x665	6.210	1/4	1/4	5/16	7/16	9/16
W14x730	6.760	1/4	1/4	5/16	7/16	9/16
W16x26	0.499	15/16	1 3/8	1-13/16	2-11/16	3 9/16
W16x31	0.592	13/16	1 1/4	1 5/8	2 7/16	3 1/4
W16x36	0.617	13/16	1 1/4	1 5/8	2 7/16	3 3/16
W16x40	0.686	13/16	1 3/16	1 9/16	2 5/16	3 1/16
W16x45	0.767	3/4	1 1/16	1 7/16	2 1/8	2 7/8
W16x50	0.846	11/16	1 1/16	1 3/8	2 1/16	2-11/16
W16x57	0.963	5/8	15/16	1 1/4	1 7/8	2 1/2
W16x67	0.936	11/16	1	1 5/16	1-15/16	2 9/16
W16x77	1.070	5/8	7/8	1 3/16	1 3/4	2 5/16
W16x89	1.220	9/16	13/16	1 1/16	1 5/8	2 1/8
W16x100	1.370	1/2	3/4	1	1 1/2	2
W18x35	0.602	13/16	1 1/4	1 5/8	2 7/16	3 1/4
W18x40	0.688	13/16	1 3/16	1 1/2	2 1/4	2 15/16
W18x46	0.786	3/4	1 1/16	1 7/16	2 1/8	2 13/16
W18x50	0.778	3/4	1 1/16	1 7/16	2 1/8	2 13/16
W18x55	0.850	11/16	1	1 3/8	2	2-11/16
W18x60	0.923	11/16	1	1 5/16	1-15/16	2 9/16
W18x65	0.997	5/8	15/16	1 1/4	1-13/16	2 7/16
W18x71	1.080	5/8	7/8	1 3/16	1 3/4	2 5/16
W18x76	0.971	5/8	15/16	1 1/4	1 7/8	2 1/2
W18x86	1.090	5/8	7/8	1 3/16	1 3/4	2 5/16
W18x97	1.220	9/16	13/16	1 1/16	1 5/8	2 1/8

W18x106	1.330	1/2	3/4	1	1 1/2	2
W18x119	1.480	1/2	3/4	15/16	1 7/16	1 7/8
W21x44	0.672	13/16	1 3/16	1 9/16	2 5/16	3 1/16
W21x50	0.754	3/4	1 1/8	1 7/16	2 3/16	2 7/8
W21x57	0.857	11/16	1	1 3/8	2	2-11/16
W21x62	0.846	11/16	1 1/16	1 3/8	2 1/16	2-11/16
W21x68	0.926	11/16	1	1 5/16	1-15/16	2 9/16
W21x73	0.989	5/8	15/16	1 1/4	1 7/8	2 7/16
W21x83	1.120	9/16	7/8	1 1/8	1-11/16	2 1/4
W21x93	1.240	9/16	13/16	1 1/16	1 5/8	2 1/8
W21x101	1.130	9/16	7/8	1 1/8	1-11/16	2 1/4
W21x111	1.240	9/16	13/16	1 1/16	1 5/8	2 1/8
W21x122	1.350	1/2	3/4	1	1 1/2	2
W21x132	1.450	1/2	3/4	1	1 7/16	1-15/16
W21x147	1.610	7/16	11/16	7/8	1 5/16	1 3/4
W24x55	0.749	3/4	1 1/8	1 7/16	2 3/16	2 7/8
W24x62	0.844	11/16	1 1/16	1 3/8	2 1/16	2-11/16
W24x68	0.837	11/16	1 1/16	1 3/8	2 1/16	2-11/16
W24x76	0.933	11/16	1	1 5/16	1-15/16	2 9/16
W24x84	1.020	5/8	15/16	1 1/4	1-13/16	2 7/16
W24x94	1.140	9/16	7/8	1 1/8	1-11/16	2 1/4
W24x104	1.070	5/8	7/8	1 3/16	1 3/4	2 5/16
W24x117	1.200	9/16	13/16	1 1/8	1 5/8	2 3/16
W24x131	1.330	1/2	3/4	1	1 1/2	2
W24x146	1.480	1/2	3/4	15/16	1 7/16	1 7/8
W24x162	1.630	7/16	11/16	7/8	1 5/16	1 3/4
W27x84	0.921	11/16	1	1 5/16	1-15/16	2 9/16
W27x94	1.030	5/8	15/16	1 3/16	1-13/16	2 3/8
W27x102	1.110	5/8	7/8	1 3/16	1 3/4	2 5/16
W27x114	1.230	9/16	13/16	1 1/16	1 5/8	2 1/8
W27x146	1.350	1/2	3/4	1	1 1/2	2

W27x161	1.480	1/2	3/4	15/16	1 7/16	1 7/8
W27x178	1.630	7/16	11/16	7/8	1 5/16	1 3/4
W30x99	1.000	5/8	15/16	1 1/4	1-13/16	2 7/16
W30x108	1.090	5/8	7/8	1 3/16	1 3/4	2 5/16
W30x116	1.160	9/16	7/8	1 1/8	1-11/16	2 1/4
W30x124	1.240	9/16	13/16	1 1/16	1 5/8	2 1/8
W30x132	1.320	9/16	13/16	1 1/16	1 9/16	2 1/16
W30x173	1.470	1/2	3/4	15/16	1 7/16	1 7/8
W30x191	1.620	7/16	11/16	7/8	1 5/16	1 3/4
W30x211	1.760	7/16	5/8	7/8	1 1/4	1-11/16
W33x118	1.080	5/8	7/8	1 3/16	1 3/4	2 5/16
W33x130	1.180	9/16	13/16	1 1/8	1 5/8	2 3/16
W33x141	1.280	9/16	13/16	1 1/16	1 9/16	2 1/16
W33x152	1.370	1/2	3/4	1	1 1/2	2
W33x201	1.580	1/2	11/16	15/16	1 3/8	1-13/16
W33x221	1.730	7/16	5/8	7/8	1 1/4	1-11/16
W33x241	1.870	7/16	5/8	13/16	1 3/16	1 9/16
W36x135	1.150	9/16	7/8	1 1/8	1-11/16	2 1/4
W36x150	1.270	9/16	13/16	1 1/16	1 9/16	2 1/16
W36x160	1.350	1/2	3/4	1	1 1/2	2
W36x170	1.430	1/2	3/4	1	1 7/16	1-15/16
W36x182	1.520	1/2	11/16	15/16	1 3/8	1 7/8
W36x194	1.620	7/16	11/16	7/8	1 5/16	1 3/4
W36x210	1.740	7/16	5/8	7/8	1 1/4	1-11/16
W36x230	1.690	7/16	11/16	7/8	1 5/16	1-11/16
W36x245	1.790	7/16	5/8	13/16	1 1/4	1 5/8
W36x260	1.900	7/16	5/8	13/16	1 3/16	1 9/16
W36x280	2.030	3/8	9/16	3/4	1 1/8	1 1/2
W36x300	2.170	3/8	9/16	3/4	1 1/16	1 7/16

ARABIAN VERMICULITE INDUSTRIES — Types MK-6/HY, MK-6/HY Extended Set, MK-6/GF, MK-10 HB, MK-10 HB Extended Set, MK-6/HB, MK-6s, Z-106, Z-106/G, Z-106/HY.

GCP KOREA INC — Types MK-6/HY, MK-6/HY Extended Set, MK-6/GF, MK-10 HB, MK-10 HB Extended Set, MK-6/HB, MK-6s, Z-106, Z-106/G, Z-106/HY.

GCP APPLIED TECHNOLOGIES INC — Types MK-6/HY, MK-6/HY Extended Set, MK-6/GF, MK-10 HB, MK-10 HB Extended Set, MK-6/HB, MK-6s, RG, Z-106, Z-106/G, Z-106/HY, MK-1000/HB, MK-1000/HB Extended Set, Z-146, Z-146PC, Z-146T, Z-156, Z-156T and Z-156PC (Types Z-146, Z-146PC, Z-146T, Z-156, Z-156PC, Z-156T also investigated for exterior use).

2. **Metal Lath** — (Required for box application - Optional for contour application) — 3.4 lb/sq yd galvanized or painted expanded steel lath. For box applications, lath shall be lapped 1 in. and tied together with No. 18 SWG galvanized steel; wire spaced vertically 6 in. O.C. For contour applications, lath is installed vertically with joints butted together and secured to the column with powder actuated fasteners located 18 inches on center at joints and as necessary to have the lath follow the column contour. As an alternate, either welded fixing or high temperature adhesive referenced "HTA Adhesive" (supplied by HTA Ltd), fixing of pins to steel column are permitted.

3. **Steel Column** — Wide flange steel columns (36 ksi yield), min/max sizes as specified above.

*** Indicates such products shall bear the UL or cUL Certification Mark for jurisdictions employing the UL or cUL Certification (such as Canada), respectively.**

Last Updated on 2019-07-12

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"