



SAFETY DATA SHEET

1. Identification

Product identifier Bituthene Liquid Membrane Part A

Other means of identification

Product Identifier 60025

Synonyms Detail Liquid

Recommended use Construction materials.

Recommended restrictions No other uses are advised.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name GCP Applied Technologies

Address 20 Moores Rd.
Malvern, PA 19355
United States

Telephone +1 866-333-3726

E-mail Not available.

Emergency phone number 3E Global Incident Hotline
1 760 476 3962
1 866 519 4752 (Toll Free)
Access Code: 336250

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Extracts (petroleum), heavy paraffinic distillate solvent		64742-04-7	15 - 40
1,3-BUTADIENE, HOMOPOLYMER, HYDROXY-TERMINATED		69102-90-5	10 - 30

Chemical name	Common name and synonyms	CAS number	%
Asphalt		8052-42-4	10 - 30
precipitated silica (amorphous)		7631-86-9	7 - 13
Glycerol, propoxylated		25791-96-2	3 - 7

Composition comments The exact concentrations of the above listed chemicals are being withheld as a trade secret. All concentrations are in percent by weight.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Foam. Dry powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store in closed original container in a dry place.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)	PEL	5 mg/m3	Mist.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
precipitated silica (amorphous) (CAS 7631-86-9)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		0.8 mg/m3	

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	TWA	0.5 mg/m3	Inhalable fume.
Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)	TWA	5 mg/m3	Inhalable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)	IDLH	2500 mg/m3
precipitated silica (amorphous) (CAS 7631-86-9)	IDLH	3000 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL)

Components	Type	Value	Form
Asphalt (CAS 8052-42-4)	Ceiling	5 mg/m3	Fume.
Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
precipitated silica (amorphous) (CAS 7631-86-9)	TWA	6 mg/m3	

Biological limit values**ACGIH Biological Exposure Indices (BEI)**

Components	Value	Determinant	Specimen	Sampling Time
Asphalt (CAS 8052-42-4)	2.5 µg/l	1-Hydroxypyrene, with hydrolysis (1-HP)	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Chemical resistant gloves.

Other

Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Semi-solid.

Color Black.

Odor Characteristic.

Odor threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling range Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not miscible.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Particle size Varies.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Chlorine. Fluorine.

Hazardous decomposition products Carbon oxides.

11. Toxicological information**Information on likely routes of exposure**

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Not known.

Components

Species

Test Results

Asphalt (CAS 8052-42-4)

Acute

Dermal

LD50

Rabbit

> 2000 mg/kg

Oral

LD50

Rat

> 5000 mg/kg

precipitated silica (amorphous) (CAS 7631-86-9)

Acute

Oral

LD50

Rat

> 22500 mg/kg

Skin corrosion/irritation

Due to partial or complete lack of data the classification is not possible.

Serious eye damage/eye irritation

Due to partial or complete lack of data the classification is not possible.

Respiratory or skin sensitization

Respiratory sensitization

Due to partial or complete lack of data the classification is not possible.

Skin sensitization

Due to partial or complete lack of data the classification is not possible.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Asphalt (CAS 8052-42-4)

2B Possibly carcinogenic to humans.

Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)

3 Not classifiable as to carcinogenicity to humans.

precipitated silica (amorphous) (CAS 7631-86-9)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Asphalt (CAS 8052-42-4)

Known To Be Human Carcinogen.

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard

Due to partial or complete lack of data the classification is not possible.

Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated "active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Carcinogenicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Asphalt (CAS 8052-42-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Asphalt (CAS 8052-42-4)

Extracts (petroleum), heavy paraffinic distillate solvent (CAS 64742-04-7)

California Proposition 65



WARNING: This product can expose you to Asphalt, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Asphalt (CAS 8052-42-4)

Listed: January 1, 1990

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 03-26-2024**Version #** 01

Disclaimer GCP Applied Technologies cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.