

# ADVA<sup>®</sup> ITM750

High-range water-reducing admixture  
ASTM C494 Type F and S

---

## Product Description

ADVA<sup>®</sup> ITM750 is a high efficiency, low addition rate polycarboxylate-based high-range water reducer designed for in-transit management of concrete workability. It is designed to impart extreme workability without segregation to the concrete.

ADVA<sup>®</sup> ITM750 is supplied as a ready-to-use liquid that weighs approximately 8.9 lbs/gal (1.1 kg/L). ADVA<sup>®</sup> ITM750 does not contain intentionally added chlorides.

## Uses

ADVA<sup>®</sup> ITM750 admixture is formulated to impart improved workability to the concrete and to achieve high early compressive strength.

ADVA<sup>®</sup> ITM750 may be used to produce concrete with very low water/cementitious ratios while maintaining normal levels of workability.

## Addition Rates

ADVA<sup>®</sup> ITM750 is an easy to dispense liquid admixture. Dosage rates can be adjusted to meet a wide spectrum of concrete performance requirements. The admixture typically meets ASTM C494 Type S requirements at 0.1 to 3 oz/100 lb (6.5 to 195 mL/100 kg) and ASTM C494 Type F requirements at 3 to 10 oz/100 lb (195 to 650 mL/100 kg) of cementitious materials. Mix proportions, cementitious content, aggregate gradations and ambient conditions will affect ADVA<sup>®</sup> ITM750 dosage requirements. Should conditions or materials require using more than the recommended addition rate, please consult your GCP Applied Technologies representative.

## Product Advantages

- Produces concrete with high levels of workability without segregation
- Reliably delivers concrete at consistent slump
- Excellent concrete rheology and handling properties
- Provides improved finishability and surface finishes
- Superior air entrainment control

## Compatibility with Other Admixtures

ADVA<sup>®</sup> ITM750 is compatible with most GCP admixtures. Pretesting of the concrete mix should be performed before use, or as conditions and materials change, in order to assure concrete performance.

For concrete that requires air entrainment, the use of an ASTM C260 air-entraining agent (such as DARAVAIR® or DAREX® product lines) is recommended to provide suitable air void parameters for freeze-thaw resistance. Please consult your GCP Applied Technologies representative for guidance.

## Packaging & Handling

ADVA® ITM750 is a yellowish brown liquid available in bulk, delivered by metered trucks, in totes and drums.

ADVA® ITM750 will freeze at approximately 32 °F (0 °C) but will return to full functionality after thawing and thorough mechanical agitation.

## Dispensing

A complete line of accurate, automatic dispensing equipment is available to plant dose ADVA® ITM750 into the concrete. ADVA® ITM750 can also be added to the concrete via the VERIFI® In-Transit Concrete Management system on ready mix trucks.

[gcpat.com](http://gcpat.com) | North America Customer Service: 1 877-4AD-MIX1 (1 877-423-6491)

We hope the information here will be helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

ADVA, DARAVAIR, DAREX, and VERIFI are trademarks, which may be registered in the United States and/or other countries, of GCP Applied Technologies Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2019 GCP Applied Technologies Inc. All rights reserved.

GCP Applied Technologies Inc., 62 Whittemore Avenue, Cambridge, MA 02140 USA.

In Canada, GCP Canada, Inc., 294 Clements Road, West, Ajax, Ontario, Canada L1S 3C6.

This document is only current as of the last updated date stated below and is valid only for use in the United States. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on [www.gcpat.com](http://www.gcpat.com). Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2019-09-17

[gcpat.com/solutions/products/adva-high-range-water-reducers/adva-itm750](http://gcpat.com/solutions/products/adva-high-range-water-reducers/adva-itm750)